



<b>Dimensions</b>	90 x 19 mm
<b>Operating Frequency</b>	Global (860 – 960 MHz)
<b>RF Protocol</b>	ISO-18000-6C, EPC Class 1, Gen 2
<b>Chip</b>	NXP UCODE 7xm+
<b>EPC Memory</b>	448 bit
<b>TID Memory</b>	48-bit unique serialized TID number
<b>USER Memory</b>	2048 bit

**Common Applications**  
 Glass & Automobile Tracking  
 Race Timing  
 Miscellaneous Applications

Toll free US 866-903- RFID (7343) / [rfid.info@averydennison.com](mailto:rfid.info@averydennison.com)  
 International +1-770-965-0807

PART NUMBER	RF600917	RF600855
Format	Dry Inlay	Pressure Sensitive Inlay
Antenna dimensions (CDxMD)	3.543 x 0.748 in (90 x 19 mm)	3.543 x 0.748 in (90 x 19 mm)
Die-cut dimensions	N/A	3.67 x 0.87 in (93.175 x 22.175 mm)
Inlay substrate material	White PET	White PET
Inlay-to-liner adhesive	N/A	S-490 (FASSON)
Liner material	N/A	1.5M Clear PET
Face Sheet	N/A	N/A
Standard pitch	1.25 in (31.8 mm)	1.25 in (31.8 mm)
Standard web width	3.875 in (98.4 mm)	3.875 in (98.4 mm)
Total thickness over chip	10-12 mils (254-305 microns)	11-14 mils (279-356 microns)
Operating temperature	-40 to 185F (-40 to 85C)	-40 to 185F (-40 to 85C)
RoHS	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant
Quality assurance	100% read tested with-of-tolerance inlay marked	100% read tested with-of-tolerance inlay marked
Un-wind direction	Inlay-side Out	PS Inlay-side Out
Core size with adaptor insert	3 in (76.2 mm)	3 in (76.2mm)
Maximum roll outer diameter (not to exceed)	17 in (431.8 mm)	13 in (330.2mm)
Average # of units per roll	20,000 good +/- 10%	10,000 good +/- 10%
Rev	00	00

**Care and handling:** RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

**Applications:** This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

**Warranty:** Please refer to Avery Dennison RFID standard terms and conditions.

**Product Information:** Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

**Trademark statement:** Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit [www.rfid.averydennison.com](http://www.rfid.averydennison.com).