

AD-385u8 NEL

Overview

Frequency Band

UHF 860 - 960 MHz

Chip

NXP UCODE 8

Antenna Dimensions

30 x 50 mm / 1.18 x 1.97 in

International Standard

ISO/IEC 18000-63 Type C

Industry Segments

Apparel
Logistics

Applications

Supply Chain Management
Home Essentials
Brand Protection

RoHs

EU Directive 2011/65/EU and
2015/863 Compliant



Combining performance and versatility

AD-385u8 NEL from Avery Dennison is a high performing inlay suitable for a wide variety of RFID tagging applications. It features the UCODE 8 chip by NXP.

The Gen2 UHF RAIN RFID inlay perfectly integrates with a wide variety of RFID tagging applications, including supply chain, inventory & logistics, apparel and home essentials.

AD-385u8 features the UCODE 8 chip that is equipped with 128 bits of EPC memory, including a 32-bit access password and 32-bit kill password to permanently disable the tag. A 96-bit Tag Identifier (TID) is factory locked with a 48-bit unique serial number factory-encoded into the TID.

AD-385u8 NEL is also available in wide-edge leading (WEL) format. Delivery formats include dry, wet and label / sticker.

Like all RFID products from Avery Dennison Intelligent Labels, AD-385u8 NEL inlays are manufactured according to the industry's highest quality standards, as confirmed by the RFID Lab at Auburn University: The inspection body awarded Avery Dennison its first comprehensive and significant ARC accreditation for quality.

Technical features

Chip	NXP UCODE 8	
EPC and User Memory	128-bit and n/a	
TID Memory	96-bit / 48-bit unique serial number	
Product Code	RF601408	RF100658
Delivery Format	Wet inlay	
Die-cut Dimension	34 x 54 mm / 1.34 x 2.13 in	
Inlay Substrate	PET	40# Paper
Face Sheet	-	TT2C (FASSON®) Bright White
Total Thickness	12 - 14 mils / 300 - 350 microns	16 - 18 mils / 412 - 463 microns
Standard Pitch	63.5 mm / 2.5 in	
Web Width	38 mm / 2 in	
Core Size	76 mm / 3 in	
Operating Temperature	-40 °C to 85 °C -40 °F to 185 °F	
On-Metal	Non metal	
Certificate	ARC	

Contact information

rfid.averydennison.com/contact

North America: +1-866-903-7343 (toll free US)

International: +1-678-617-2359

RoHS

© 2020 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison Intelligent Labels standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

