Avery Dennison Smartrac Product Data Sheet

AD-834 U9

Overview

Frequency Band UHF 860 - 960 MHz

Chip UCODE 9

Antenna Dimensions \emptyset 13 mm / \emptyset .512 in

International Standard ISO/IEC 18000-63 Type C

Industry Segments Non-food Retail

Applications Beauty and Personal Care Small Apparel

RoHS

EU Directive 2011/65/EU and Directive (EU) 2015/863

REACH

Regulation (EC) No. 1907/2006





Efficient custom inlay for beauty products

AD-834 U9 inlay was developed for beauty products, and is perfectly suited for personal care and small apparel tagging as well.

Digitization of beauty products by RFID tagging can offer customers a seamless shopping experience by merging the digital and physical retail worlds, and ensure supply-chain integrity to safeguard brand value. In addition, beauty retail channels like pick-up-on-curb and virtual stores are proliferating. More than ever, consumers of beauty products expect to buy what they want anytime, anywhere, wholly on their terms, creating a greater need for a seamless shopping experience - which is made easier by digitizing products to manage the supply chain efficiently.

The inlay's antenna measures 13 mm in diameter, and can achieve read distances of up to seven meters on a variety of surfaces including plastic, glass and cardstock. The product is available in dry inlay, wet inlay and paper label delivery formats. AD-834 U9 features NXP's UCODE 9 chip that is equipped with 96-bit of EPC memory, including a 96-bit Tag IDentifier (TID) with a 48-bit unique serial number factory-encoded into the TID. The inlay is available now.

AD-834 U9 complies with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, especially in the retail environment. Like all Avery Dennison products, it is manufactured to the industry's highest quality standards.

rfid.averydennison.com

Technical features

Chip	NXP UCODE 9		
EPC and User Memory	96-bit EPC / -		
TID Memory	96-bit / 48-bit unique serial number		
Product Code	3008125 / IL-604094	3008095 / IL-604075	3008215 / IL-604157
Delivery Format	Dry inlay	Wet inlay	Label
Die-Cut Dimension	-	Ø 15 mm / 0.59 in	Ø 16 mm / 0.630 in
Inlay Substrate	38µm Opaque PET	38µm Opaque PET	38µm Opaque PET
Face Sheet	-	-	BW0053
Total Thickness	6 - 7 mils / 154 -290 µm	9 - 12 mils / 241 - 295 µm	13 - 16 mils / 329 - 401 µm
Standard Pitch	25.4 mm / 1.0 in	25.4 mm / 1.0 in	31.8 mm / 1.252 in
Web Width	50.8 mm / 2.0 in	50.8 mm / 2.0 in	24 mm / 0.945 in
Core Size	76 mm / 3 in	76 mm / 3 in	76 mm / 3 in
Quantity / Reel	5,000 pcs/reel	5,000 pcs/reel	5,000 pcs/reel
Operating Temperature	-40 °C to 85 °C -40 °F to 185 °F		
Certificates	N/A		

Orientation sensitivity



All graphs are indicative: performance in real life applications may vary.

Read range





© 2022 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only. Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

