

Band

Overview

Frequency Band

HF 13.56 MHz

Chip

NXP ICODE ILT-M

Antenna Dimensions

23 x 70 mm / 0.91 x 2.76 in

International Standard

ISO18000-3 Mode 3

Industry Segments

Media and Document Management

Applications

Documents and Files

RoHS

EU Directive 2011/65/EC and
Directive (EU) 2015/863

REACH

Regulation (EC) No 1907/2006



Top performance tag for document management

Our Band inlays and tags featuring NXP ICODE ILT-M IC are designed to allow close stacking or contact that confuses other inductively coupled HF and LF tags.

Band tags and inlays with NXP ICode ILT-M ICs have a slim antenna design to fit the margin of documents to not interfere with document contents. The tags provide excellent performance in document and item identification where close stacking occurs, which is a challenging environment for other passive RFID protocols. Moreover Band tags and inlays also work well in RFID applications where very fast inventory of multiple RFID tags in the field occurs. In these cases, Band tags offer performance approaching UHF EPC Class 1 Gen 2. Overall RFID inlays and tags using ILT ICs are cost efficient than any other RFID inlays designed for close stacking.

Our inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management. This ensures a reliable and state-of-the-art product that meets a variety of application needs, where high performance is a critical parameter.

Technical features

Chip	NXP ICODE ILT-M	
EPC and User Memory	240-bit and 512-bit	
Product Code	3002993	3003031
Delivery Format	Wet inlay	Dry inlay
Die-Cut Dimension	25 x 72 mm / 0.98 x 2.84 in	-
Inlay Substrate	PET	PET
Face Sheet	Clear PET	Clear PET
Total Thickness	136 µm	116 µm
Standard Pitch	80 mm / 3.150 in	80 mm / 3.150 in
Web Width	30 mm / 1.18 in	30 mm / 1.18 in
Core Size	76 mm / 3 in	76 mm / 3 in
Quantity / Reel	1500 pcs/reel 3000 pcs/box	1500 pcs/reel 3000 pcs/box
Operating Temperature	-40 °C to 85 °C -40 °F to 185 °F	

All graphs are indicative: performance in real life applications may vary.

Contact information

rfid.averydennison.com/contact

+1-678-617-2359

Connect with us on:



© 2021 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

