

# AD Dogbone<sup>®</sup> UCODE G2iL

## Overview

---

**Frequency Band**

UHF 860 - 960 MHz

---

**Chip**

NXP UCODE G2iL

---

**Antenna Dimensions**

88 x 24 mm / 3.47 x 0.94 in

---

**International Standard**

ISO 18000-6C, EPC Class 1 Gen 2

---

**Industry Segments**

Automotive  
Industrial Applications  
Sports and Events

---

**Applications**

Sports Timing  
Glass and Automobile Tracking  
Inventory

---

**RoHS**

EU Directive 2011/65/EC and  
Directive (EU) 2015/863

---

**REACH**

Regulation (EC) No. 1907/2006



## Excellent global performance even on difficult-to-tag materials

Our AD Dogbone<sup>®</sup> inlays and tags are designed for global supply chain, industrial and RTI applications, offer excellent performance in demanding environments and on different materials.


AD Dogbone<sup>®</sup> inlays and tags have a good tolerance to the detuning effect of high dielectric materials, providing effective global performance even on difficult-to-tag materials. They are available with the NXP UCODE G2iL chip that offers 128 bits of EPC memory. The inlay is size-optimized for 100 mm / 4 inch wide converted labels, and is available in dry, wet and label / sticker delivery formats.

Our inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, enhancing RFID usage for difficult-to-tag materials.


## Technical features

Chip	NXP UCODE G2iL	
EPC and User Memory	128-bit	
TID Memory	64-bit / 32-bit unique serial number	
Product Code	3002037 / IL-602611	3002038 / IL-602612
Delivery Format	Wet inlay+	Label / sticker
Die-Cut Dimension	97 x 27 mm / 3.819 x 1.06 in	97 x 27 mm / 3.819 x 1.06 in
Face Sheet	Clear PET 12	Opaque Matt Paper 79
Standard Pitch	30 mm / 1.181 in	-
Web Width	100 mm / 3.937 in	100 mm / 3.937 in
Core Size	76 mm / 3in	76 mm / 3in
Quantity / Reel	5,000 pcs / reel 10,000 pcs / box	3,000 pcs / reel 6,000 pcs / box
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F	

## Orientation sensitivity



## Read range



All graphs are indicative: performance in real life applications may vary.

### Contact information

rfid.averydennison.com/contact  
North America: +1-866-903-7343 (toll free US)  
International: +1-678-617-2359

Connect with us on:



© 2021 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

**Warranty:** Please refer to Avery Dennison standard terms and conditions: [rfid.averydennison.com/termsandconditions](https://www.averydennison.com/termsandconditions)

**Care and handling:** RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

**Applications:** This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

